

Description:

Motor: PMSM (Permanent Magnet Synchronous Motor) 48V/1kW (2pcs x500W)
Max Power: 1000W
Controller: PMSMmotor controller, 2pcs x48V/28A
Dual 48V 20Ah Lithium Battery
Gear speed control setting Panel
Charger input/Output: 110V-/3A,
Charging Time: 6-8hours/1pcs charger
Passenger: 1 person
Dimension LxWxH: 50"x32"X46"
Range: 24-28 Miles- Depending on terrain, driving.
Max.Speed: 8 and 22Mpr
Utility 4 wheel, rear wheel drive
NetWeight: 168 lbs
Min. Ground Clearance: 4'
Max Climbing: 30 degree
Max.Load: 340 lbs
Driving System: 2 Wheel Hub Motor Driving
Braking System: F/R Four wheel Disc Brakes- Hyd
Front and rear brake pull lever controls
Suspensions: F/R Swing arm with Spring
Handlebar: Aluminium Alloy, foldable
Chassis: High strength steel
Square tube welded structure
Electrical horn
Display: LCD control screen
80/65-6 Scooter Tire,Front tires Wheel Aluminum hub,
10 Inch Replacement Thickened Pneumatic 255x80 10x3.0 inner tubes(off road)
Wheel Rim: 6 inch, Aluminum Alloy
Package: Steel rack with strong Weld
FLAT ROAD STANDING Device- (All Terrain 4" clearance recreation Vehicle)
Thumb push speed trotter
Reverse touch button
Carring Cart prepared pulling slot sleeve
Aluminum corrugated anti slip coated platform
USB-power connection phone charging
Foldable handle bars locking swival-
Emergency warning strob Lights - **Optional**
Cary case back side containers-**Optional**
Front utility /first aid carry container- **Optional**
Reinforced springs to carry up to 340lbs
Phone holder-
Cup Holder- **Optional**
Flashlight and secure holder - **Optional**
Rear view mirror with light- **Optional**
Back tire guards with lights -**Optional**
Fire Extinguisher- **Optional**
Back Rest support - **Optional**

Chariot360 2.0



\$5,800.00

To be used in various applications, such as security perimeter, Industrial and warehouse, Emergency assist, work mobile usage, carry usage,, etc...Prepared for Personal use